

HOFFMAN

BC SERIES

DRY CLEANING
AIR-OPERATED PRESS



The BC Series delivers top-notch pressing at a reasonable cost. With its compact footprint and rapid single-cylinder operation, it facilitates speedy and convenient garment pressing even in tight spaces. Encounter the peace of mind and comfort ensured by our simplified pneumatic control system and ergonomic design.

EXCEPTIONALLY FAST, HIGH-QUALITY PRESSING

With meticulously crafted cylinder.

BUILT FOR A LONG LIFE

Including robust heads, frames, linkages, and superior rust protection.

MINIMAL FLOOR SPACE REQUIRED

With a compact frame.



EASY INSTALLATION AND MAINTENANCE

Powered by a simplified pneumatic control system.

OPERATOR'S COMFORT

Guaranteed by ergonomic soft-touch operating buttons and foot pedal.

MULTIPLE HEAD/BUCK OPTIONS

Available to suit your application.

AVAILABLE OPTIONS

- Built-in electric steam generator (-SC)
- Built-in buck vacuum motor (1.1kW, 220V/50-60Hz/1)
- Buck blow
- Inverted vacuum/steam pedals
- Steam spotting gun (220V/50-60Hz/1)
- Steam/air gun (220V/50-60Hz/1)
- Water spray gun w/ condenser
- Adjustable head-release timer (0.11kW, 220V/50-60Hz/1)
- Electric heated steam iron w/ steam regulator and iron stand (0.8kW, 220V/50-60Hz/1)
- All steam iron and iron stand
- Stainless steel table
- Swing-away sleeve arm
- Swing-away sleeve arm w/ vacuum
- Safety guard

SPECIFICATIONS

	Unit	BC42	BC45	BC42HH	BC46	BCM1	BCM3
Vacuum Connection Size (NPT)	in	1.25	1.25	1.25	2	1.25	1.25
Steam Inlet (NPT)	in	1/2	1/2	1/2	1/2	1/2	1/2
Steam Outlet (NPT)	in	1/2	1/2	1/2	1/2	1/2	1/2
Steam Working Pressure	psi (MPa)	85 (0.59)	85 (0.59)	85 (0.59)	85 (0.59)	85 (0.59)	85 (0.59)
Steam Consumption	lb/hr (kg/hr)	30 (13.6)	30 (13.6)	30 (13.6)	30 (13.6)	30 (13.6)	30 (13.6)
Air Inlet (NPT)	in	3/8	3/8	3/8	3/8	3/8	3/8
Air Working Pressure	psi (MPa)	80 (0.55)	80 (0.55)	80 (0.55)	80 (0.55)	80 (0.55)	80 (0.55)
Air Consumption	L/cycle	20	20	20	20	20	20
Table Length	in (mm)	51 (1295.4)	51 (1295.4)	51 (1295.4)	48 (1219)	36 (914)	36 (914)
Dimensions (Width, Depth, Height)							
Uncrated	in	51 x 39 x 63			48 x 39 x 63	36 x 39 x 63	
	mm	1295 x 991 x 1600			1219 x 991 x 1600	1295 x 990 x 1600	
Crated	in	55 x 43 x 60				39 x 43 x 60	
	mm	1400 x 1100 x 1524				1000 x 1100 x 1524	
Approximate Weight							
Uncrated	lb (kg)	573 (260)	595 (270)	573 (260)	628 (285)	441 (200)	441 (200)
Crated	lb (kg)	661 (300)	683 (310)	661 (300)	717 (325)	507 (230)	507 (230)



BUCK DIMENSIONS (BEFORE PADDING)

