HOFFMAN

BC SERIES

DRY CLEANING AIR-OPERATED PRESS



The BC Series delivers top-notch pressing at a reasonable cost. With its compact footprint and rapid single-cylinder operation, it facilitates speedy and convenient garment pressing even in tight spaces. Encounter the peace of mind and comfort ensured by our simplified pneumatic control system and ergonomic design.

EXCEPTIONALLY FAST, HIGH-QUALITY PRESSING

With meticulously crafted cylinder.

BUILT FOR A LONG LIFE

Including robust heads, frames, linkages, and superior rust protection.

MINIMAL FLOOR SPACE REQUIRED

With a compact frame.

RELEASE

EASY INSTALLATION AND MAINTENANCE

Powered by a simplified pneumatic control system.

OPERATOR'S COMFORT

Guaranteed by ergonomic soft-touch operating buttons and foot pedal.

MULTIPLE HEAD/BUCK OPTIONS

Available to suit your application.

AVAILABLE OPTIONS

- · Electric steam generator
- · Built-in buck vacuum motor (1.1kW, 220V/50-60Hz/1)
- · Buck blow
- · Inverted vacuum/steam pedals
- · Steam spotting gun (230V/50-60Hz/1)
- · Steam/air spotting gun (230V/50-60Hz/1)
- · Water spray gun w/ condenser
- · Adjustable head-release timer (0.11kW, 220V/50-60Hz/1)

- · Electric heated steam iron w/ steam regulator and iron stand (1.1kW, 220V/50-60Hz/1)
- · All steam iron and iron stand
- · Stainless steel table
- · Swing-away sleeve arm
- · Swing-away sleeve arm w/ vacuum
- · Insulated fabric head cover
- · Safety guard



| SPECIFICATIONS | | | | | | | |
|--------------------------------------|---------------|-------------------------------------|-------------|-------------|-----------|--------------------|-----------|
| | Unit | BC42 | BC45 | вс42нн | BC46 | всмі | всм3 |
| Vacuum Connection Size (NPT) | in | 1.25 | 1.25 | 1.25 | 2 | 1.25 | 1.25 |
| Steam Inlet (NPT) | in | 1/2 | 1/2 | 1/2 | 1/2 | 1/2 | 1/2 |
| Steam Outlet (NPT) | in | 1/2 | 1/2 | 1/2 | 1/2 | 1/2 | 1/2 |
| Steam Working Pressure | psi (MPa) | 85 (0.59) | 85 (0.59) | 85 (0.59) | 85 (0.59) | 85 (0.59) | 85 (0.59) |
| Steam Consumption | lb/hr (kg/hr) | 30 (13.6) | 30 (13.6) | 30 (13.6) | 30 (13.6) | 30 (13.6) | 30 (13.6) |
| Air Inlet (NPT) | in | 3/8 | 3/8 | 3/8 | 3/8 | 3/8 | 3/8 |
| Air Working Pressure | psi (MPa) | 80 (0.55) | 80 (0.55) | 80 (0.55) | 80 (0.55) | 80 (0.55) | 80 (0.55) |
| Air Consumption | L/cycle | 20 | 20 | 20 | 20 | 20 | 20 |
| Table Length | in (mm) | 51 (1295.4) | 51 (1295.4) | 51 (1295.4) | 48 (1219) | 36 (914) | 36 (914) |
| Dimensions (Width, Depth, Height) | | | 1 | | | | |
| Uncrated | in | 51 x 39 x 63 48 x 39 x 63 | | | | 36 x 39 x 63 | |
| | mm | 1295 x 991 x 1600 1219 x 991 x 1600 | | | | 1295 x 990 x 1600 | |
| Crated | in | 55 x 43 x 60 | | | | 39 x 43 x 60 | |
| | mm | 1400 x 1100 x 1524 | | | | 1000 x 1100 x 1524 | |
| Approximate Weight | | | | | | | |
| Uncrated | lb (kg) | 573 (260) | 595 (270) | 573 (260) | 628 (285) | 441 (200) | 441 (200) |
| Crated | lb (kg) | 661 (300) | 683 (310) | 661 (300) | 717 (325) | 507 (230) | 507 (230) |



BUCK DIMENSIONS (BEFORE PADDING)







