

HOFFMAN IMPERIAL SERIES

Drapery & Flat Work
Presses
DO · Dual-Operator



The Imperial Series is designed for professional finishing of drapes, sheets, linens, and other flat work. With large pressing surfaces, durable construction, and efficient operator controls, these presses deliver consistent performance for commercial laundries, dry cleaners, hotels, and institutional facilities.

TWO-OPERATOR PRODUCTIVITY

Operator stations at both ends support efficient loading, positioning, and unloading of large items.



Photo shown: DO-8

EFFICIENT DRAPE HANDLING

Deep front and rear troughs provide ample space for positioning and handling long drapes throughout the pressing process.

FULL-LENGTH PRESSING

Extra-long pressing surfaces accommodate full-length drapes and other large flat work with fewer repositioning steps.

CONSISTENT FINISHING

Controlled steam and vacuum help deliver smooth, consistent results across a variety of flat work.

AVAILABLE OPTIONS

- Flat or Curved Head
- Digital Timer (0.11kW)
- Third Center Close Buttons
- Latching Vacuum

SPECIFICATION	UNIT	DO-7	DO-8
Pressing Surface	in (mm)	24 x 96 (610 x 2438)	29 x 110 (737 x 2794)
Steam Inlet	in	1/2	1/2
Steam Outlet	in	1/2	1/2
Air Inlet	in	3/8	3/8
Vacuum Connection	in	2 NPT Female (2 places)	2 NPT Female (2 places)
Steam Working Pressure	psi (bar)	80–100 (5.5–6.9)	80–100 (5.5–6.9)
Air Working Pressure	psi (bar)	80 (5.5)	80 (5.5)
Steam Consumption	lb/hr (kg/hr)	128 (58.1)	160 (72.6)
Air Consumption	ft ³ /cycle (L/cycle)	1.23 (34.8)	1.23 (34.8)
Dimensions (WxDxH)			
Uncrated	in (mm)	121 x 64.5 x 49.2 (3073 x 1638 x 1249)	135 x 64.5 x 49.2 (3429 x 1638 x 1249)
Approximate Weight			
Uncrated	lb (kg)	3450 (1,565)	3550 (1,610)
Crated	lb (kg)	4450 (2,018)	4550 (2,064)



hoffman-ny.com
Equipment is subject to manufacturer's standard warranty. Accuracy of illustration and description of equipment shown herein applies to product as manufactured at time of publication.
© 2026 UnityLab Corp. All Rights Reserved. HOFFMAN® is a registered trademark of UnityLab Corp.
Rev. 09/2026